

<b>Vehicle model</b>	DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16	DAILY 2.3 30S12 / 30S14 / 30S16 / 33S12 / 33S14 / 33S16 35S12 / 35S14 / 35S16 / 35C12 / 35C14 / 35C16
<b>Year</b>	(09/2019>)	(09/2019>)
<b>Engine Type</b>	F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)	F1AGL411H (Euro 6) F1AGL411J (Euro 6) F1AGL411G (Euro 6)
<b>CV(kW) @ rpm</b>	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600
<b>N. of cylinders/cm3</b>	4 / 2.287	4 / 2.287
<b>Volts</b>	12	12
<b>Air Conditioning</b>	Vehicles with or without A/C	Vehicles with or without A/C
<b>Recommended fittings</b>	Suction	Discharge
<b>Compressors type</b>	Whisperpower 3.5kW / 230V	Whisperpower 3.5kW / 230V
<b>Comments</b>	<ul style="list-style-type: none"> <li>- "E"=TM / QUE / UNICLA; "S"=SAN DEN</li> <li>- "S" only for SD7H15 / SD7L15</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.</li> <li>- Can be fit on AWD vehicles</li> <li>- Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine</li> <li>- Kit for ISRKA alternator or dimensionally similar</li> </ul>	<ul style="list-style-type: none"> <li>- "E"=TM / QUE / UNICLA; "S"=SAN DEN</li> <li>- "S" only for SD7H15 / SD7L15</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.</li> <li>- Can be fit on AWD vehicles</li> <li>- Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine</li> <li>- Kit for ISRKA alternator or dimensionally similar</li> </ul>
<b>Clutch type</b>	Without clutch pulley	Without clutch pulley
<b>Kit No.</b>	KA19095005	KA19095005
<b>Last update</b>	2020-11-11	2020-11-11

<b>Vehicle model</b>	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - <b>CNG / NPW</b>	DAILY 3.0 35S15 / 35C15 / 50C15 / 65C15 / 70C15 35S17 / 35C17 / 50C17 / 65C17 / 70C17
<b>Year</b>	(09/2014>)	(09/2014>)
<b>Engine Type</b>	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) <b>F1CFA401A*A (CNG)</b>	F1CFL411J*C (Euro 5b+) F1CFL411H*C (Euro 5b+)
<b>CV(kW) @ rpm</b>	150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)	146 (107) @ 3.500 170 (125) @ 3.500
<b>N. of cylinders/cm3</b>	4 / 2.998	4 / 2.998
<b>Volts</b>	12	12
<b>Air Conditioning</b>	Vehicles with or without A/C	Vehicles with or without A/C
<b>Recommended fittings</b>	Suction Discharge	Suction Discharge
<b>Compressors type</b>	Whisperpower 3.5kW / 230V	Whisperpower 3.5kW / 230V
<b>Comments</b>	<ul style="list-style-type: none"> <li>- RWD= Rear wheel drive</li> <li>- According to bodybuilder indications, the power take off is not suitable for the automatic gear box.</li> <li>- Can be fit in right hand drive vehicles</li> <li>- Requires high idle - CABADP - when the vehicle is equipped with the Start &amp; Stop option - STOSTA</li> <li>- Kit for ISRKA alternator or dimensionally similar</li> </ul>	<ul style="list-style-type: none"> <li>- RWD= Rear wheel drive</li> <li>- According to bodybuilder indications, the power take off is not suitable for the automatic gear box.</li> <li>- Can be fit in right hand drive vehicles</li> <li>- Requires high idle - CABADP - when the vehicle is equipped with the Start &amp; Stop option - STOSTA</li> <li>- Kit for ISRKA alternator or dimensionally similar</li> </ul>
<b>Clutch type</b>	Without clutch pulley Poly-V 8pk Ø59 2.576 rpm (idle speed)	Without clutch pulley Poly-V 8pk Ø59 2.576 rpm (idle speed)
<b>Kit No.</b>	KA19055004	KA19055004
<b>Last update</b>	2019-09-30	2019-09-30

<b>Vehicle model</b>	DAILY 3.0 35C15 / 40C15 / 50C15/ 65C15/70C15 35S17 / 35C17 / 40C17 / 50C17 / 65C17 / 70C17				
<b>Year</b>	(11/2011>)				
<b>Engine Type</b>	F1CE3481J (Euro 5) F1CE3481K (Euro 5)				
<b>CV(kW) @ rpm</b>	146 (107) @ 3.500 170 (125) @ 3.500				
<b>N. of cylinders/cm3</b>	4 / 2.998				
<b>Volts</b>	12				
<b>Air Conditioning</b>	Vehicles with or without A/C				
<b>Recommended fittings</b>	Suction	Discharge			
<b>Compressors type</b>	Whisperpower 3.5kW / 230V				
<b>Comments</b>	<ul style="list-style-type: none"> <li>- RWD= Rear wheel drive</li> <li>- According to bodybuilder indications, the power take off is not suitable for the automatic gear box.</li> <li>- Can be fit in right hand drive vehicles</li> <li>- Requires high idle - CABADP - when the vehicle is equipped with the Start &amp; Stop option - STOSTA</li> <li>- Kit for ISRKA alternator or dimensionally similar</li> </ul>				
<b>Clutch type</b>	Without clutch pulley				
	Poly-V 8pk Ø59 2.576 rpm (idle speed)				
<b>Kit No.</b>	KA19055004				
<b>Last update</b>	2019-09-30				