









Vehicle model	LF150 / LF180 / LF210		LF150 / LF180 / LF210		LF150 / LF180 / LF210		LF150 / LF180 / LF210		LF220 / LF250 / LF280 LF230 / LF260 / LF290 / LF320		LF220 / LF250 / LF280 LF230 / LF260 / LF290	
Year	(2014>)		(2014>)		(2014>)		(2014>)		(2014>)		(2014>)	
Engine Type	PX-5 112 (Euro 6) PX-5 135 (Euro 6) PX-5 157 (Euro 6)		PX-5 112 (Euro 6) PX-5 135 (Euro 6) PX-5 157 (Euro 6)		PX-5 112 (Euro 6) PX-5 135 (Euro 6) PX-5 157 (Euro 6)		PX-5 112 (Euro 6) PX-5 135 (Euro 6) PX-5 157 (Euro 6)		PX-7 164,172 (Euro 6) PX-7 186,194 (Euro 6) PX-7 208, 217 (Euro 6)		PX-7 164,172 (Euro 6) PX-7 186,194 (Euro 6) PX-7 208, 217 (Euro 6)	
CV(kW) @ rpm	152 (112) @ 2.300 184 (135) @ 2.300 213 (157) @ 2.300		152 (112) @ 2.300 184 (135) @ 2.300 213 (157) @ 2.300		152 (112) @ 2.300 184 (135) @ 2.300 213 (157) @ 2.300		152 (112) @ 2.300 184 (135) @ 2.300 213 (157) @ 2.300		220-230 (162) @ 2.300 250-260 (184) @ 2.300 280-290 (206) @ 2.300 320 (235) @ 2.300		220-230 (162) @ 2.300 250-260 (184) @ 2.300 280-290 (206) @ 2.300	
N. of cylinders/cm3	4 / 4.500		4 / 4.500		4 / 4.500		4 / 4.500		6 / 6.690		6 / 6.690	
Volts	24		24		24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		QP 25		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- "E"=TM / QUE / UNICLA - Can be fit in right hand drive vehicles - The vehicle must be equipped with special option DAF-006785. Attention, the option 006785 cannot be ordered when the truck is equipped with AS Tronic transmission.		- Can be fit in right hand drive vehicles		- Can be fit in right hand drive vehicles		- Can be fit in right hand drive vehicles		- The vehicle must be equipped with special option DAF. - Not suitable for vehicles with "Generator Option" - Can be fit in right hand drive vehicles		- Can be fit in right hand drive vehicles - Not to be used on 18 or 19 ton vehicles	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley		Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley		Without clutch pulley	
	Poly-V 8K Ø119 4.850 rpm	Poly-V 8K Ø142 4.060 rpm	2A Ø135 3.100 rpm		1B Ø150 3.000 rpm	1B Ø150 3.000 rpm	1B Ø150 3.600 rpm		2A Ø135 3.480 rpm		2A Ø135 3.480 rpm	
Kit No.	KC18020454	KC18020454E	KC14050362		KC14050361	KC14050361E	KC21090531	KC21090531E	KC12070284		KC14020349	
Last update	2018-03-27		2014-07-08		2014-07-08		2022-02-15		2015-06-30		2014-07-18	

Vehicle model	LF220 / LF250 / LF280 LF230 / LF260 / LF290		LF220 / LF250 / LF280 LF230 / LF260 / LF290		FA LF45.140 / FA LF45.160 FA LF45.180 / FA LF45.210		FA LF45.140 / FA LF45.160 FA LF45.180 / FA LF45.210		LF45.220 / LF45.250 / LF55.220 LF55.250 / LF55.280 / LF55.300		LF45.220 / LF45.250 / LF55.220 LF55.250 / LF55.280 / LF55.300	
Year	(2014>)		(2014>)		(2012>)		(2012>)		(2012>)		(2012>)	
Engine Type	PX-7 164,172 (Euro 6) PX-7 186,194 (Euro 6) PX-7 208,217 (Euro 6)		PX-7 164,172 (Euro 6) PX-7 186,194 (Euro 6) PX-7 208,217 (Euro 6)		Paccar FR103 (Euro 5) Paccar FR118 (Euro 5) Paccar FR136 (Euro 5)		Paccar FR103 (Euro 5) Paccar FR118 (Euro 5) Paccar FR136 (Euro 5) Paccar FR152 (Euro 5)		Paccar GR165 (Euro 5) Paccar GR184 (Euro 5) Paccar GR210 (Euro 5) Paccar GR220 (Euro 5)		Paccar GR165 (Euro 5) Paccar GR184 (Euro 5) Paccar GR210 (Euro 5)	
CV(kW) @ rpm	220-230 (162) @ 2.300 250-260 (184) @ 2.300 280-290 (206) @ 2.300		220-230 (162) @ 2.300 250-260 (184) @ 2.300 280-290 (206) @ 2.300		140 (103) @ 2.500 160 (118) @ 2.500 185 (136) @ 2.500		140 (103) @ 1.900 160 (118) @ 1.900 185 (136) @ 2.100 207 (152) @ 2.200		224 (165) @ 1.900 250 (184) @ 1.900 286 (210) @ 2.100 300 (221) @ 1.900		224 (165) @ 2.500 250 (184) @ 2.500 286 (210) @ 2.500	
N. of cylinders/cm3	6 / 6.690		6 / 6.690		4 / 4.500		4 / 4.500		6 / 6.700		6 / 6.700	
Volts	24		24		24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 21 / QP 21		QP 25		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TK-315 / TK-312 / TM-21 / QP-21		TK-315 / TK-312 / TM-21 / QP-21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can be fit in right hand drive vehicles - Not to be used on 18 or 19 ton vehicles		- Can be fit in right hand drive vehicles - Not to be used on 18 or 19 ton vehicles		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles		- The vehicle must be equipped with special option DAF: AFRU462 / AFRU519 / AFRU520 and STD engine rubber mounts. - Can be fit in right hand drive vehicles - Fittings not included in the kit		- The vehicle must be equipped with special option DAF: AFRU462 / AFRU519 / AFRU520 and STD engine rubber mounts. - Can be fit in right hand drive vehicles - Fittings not included in the kit		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley		Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	
	1B Ø150 3.150 rpm	TM 21 / QP 21 1B Ø150-3.150rpm	1B Ø150 3.750 rpm		2A Ø135 3.480 rpm		2B Ø152 / 1B Ø149 / 1B Ø150 2.597 rpm	1B Ø150 2.597 rpm	2B Ø152 / 1B Ø149 / 1B Ø150 2.597 rpm	1B Ø150 2.597 rpm	2A Ø135 3.480 rpm	
Kit No.	KC14020348	KC14020348E	KC21090530	KC21090530E	KC05100026		KC11090245	KC11090245E	KC11090245	KC11090245E	KC05100026	
Last update	2014-06-27		2022-02-15		2013-12-18		2013-06-03		2013-06-03		2013-12-18	

Vehicle model	FA LF45.140 FA LF45.160 / FA LF55.160 FA LF45.180 / FA LF55.180		FA LF45.140 FA LF45.160 / FA LF55.160 FA LF45.180 / FA LF55.180		FA LF45.140 FA LF45.160 / FA LF55.160 FA LF45.180 / FA LF55.180		FA LF45.140 FA LF45.160 / FA LF55.160 FA LF45.180 / FA LF55.180		FA LF45.220 / FA LF55.165 / FT LF55.220 FA LF45.250 / FA LF55.184 / FT LF55.250 FA LF55.210 / FT LF55.290	
Year	(2006>)		(2006>)		(2006>)		(2006>)		(2006>)	
Engine Type	Paccar FR103 (Euro 4) Paccar FR118 (Euro 4) Paccar FR136 (Euro 4)		Paccar FR103 (Euro 4-5) Paccar FR118 (Euro 4-5) Paccar FR136 (Euro 4-5)		Paccar FR103 (Euro 4) Paccar FR118 (Euro 4) Paccar FR136 (Euro 4)		Paccar FR103 (Euro 4) Paccar FR118 (Euro 4) Paccar FR136 (Euro 4)		Paccar GR165 (Euro 4) Paccar GR184 (Euro 4) Paccar GR210 (Euro 4)	
CV(kW) @ rpm	140 (103) @ 2.500 160 (118) @ 2.500 180 (132) @ 2.500		140 (103) @ 2.500 160 (118) @ 2.500 180 (132) @ 2.500		140 (103) @ 2.500 160 (118) @ 2.500 180 (132) @ 2.500		140 (103) @ 2.500 160 (118) @ 2.500 180 (132) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500	
N. of cylinders/cm3	4 / 4.500		4 / 4.500		4 / 4.500		4 / 4.500		6 / 6.700	
Volts	24		24		24		24		24	
Air Conditioning	Only Vehicles without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Only Vehicles without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15	
Comments	- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15. - Can be fit in right hand drive vehicles. - A 45° suction fitting is recommended on right hand drive vehicles.		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles - Fittings not included in the kit		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles - Fittings not included in the kit		- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15. - Can be fit in right hand drive vehicles. - A 45° suction fitting is recommended on right hand drive vehicles.	
Clutch type	<i>Without clutch pulley</i>	<i>With clutch pulley</i>	<i>Without clutch pulley</i>		<i>Without clutch pulley</i>	<i>With clutch pulley</i>	<i>Without clutch pulley</i>	<i>With clutch pulley</i>	<i>Without clutch pulley</i>	<i>With clutch pulley</i>
	Poly-V 8K Ø119 3.782 rpm	Poly-V 8K Ø157 2.886 rpm	2A Ø135 3.480 rpm		1B Ø150 3.150 rpm	1B Ø150 3.150 rpm	1B Ø150 3.150 rpm	1B Ø150 3.150 rpm	Poly-V 8K Ø119 3.782 rpm	Poly-V 8K Ø157 2.886 rpm
Kit No.	KC05100025	KC05100025E/S	KC05100026		KC13020315	KC13020315E	KC13020315-A	KC13020315-AE	KC05100025	KC05100025E/S
Last update	2013-12-18		2013-12-18		2014-05-12		2014-05-12		2013-12-18	

Vehicle model	FA LF45.220 / FA LF55.165 / FT LF55.220 FA LF45.250 / FA LF55.184 / FT LF55.250 FA LF55.210 / FT LF55.290		FA LF45.220 / FA LF55.165 / FT LF55.220 FA LF45.250 / FA LF55.184 / FT LF55.250 FA LF55.210 / FT LF55.290		FA LF45.220 / FA LF55.165 / FT LF55.220 FA LF45.250 / FA LF55.184 / FT LF55.250 FA LF55.210 / FT LF55.290	
Year	(2006>)		(2006>)		(2006>)	
Engine Type	Paccar GR165 (Euro 4-5) Paccar GR184 (Euro 4-5) Paccar GR210 (Euro 4-5)		Paccar GR165 (Euro 4) Paccar GR184 (Euro 4) Paccar GR210 (Euro 4)		Paccar GR165 (Euro 4) Paccar GR184 (Euro 4) Paccar GR210 (Euro 4)	
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500	
N. of cylinders/cm3	6 / 6.700		6 / 6.700		6 / 6.700	
Volts	24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	<i>Suction</i>		<i>Suction</i>		<i>Suction</i>	
Compressors type						
	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		TM 21 QP 21	
Comments	- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles - Fittings not included in the kit		- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles - Fittings not included in the kit	
Clutch type	Without clutch pulley		Without clutch pulley		Without clutch pulley	
	2A Ø135 3.480 rpm		1B Ø150 3.150 rpm		1B Ø150 3.150 rpm	
Kit No.	KC05100026		KC13020315	KC13020315E	KC13020315-A	KC13020315-AE
Last update	2013-12-18		2014-05-12		2014-05-12	

Vehicle model	FA LF45.130 FA LF45.150 FA LF45.170 / FA LF55.170		FA LF45.130 FA LF45.150 FA LF45.170 / FA LF55.170		FA LF45.180 / FA LF55.180 / FT LF55.180 / FAN LF55.180 FA LF45.220 / FA LF55.220 / FT LF55.220 / FAN LF55.220 FA LF55.250 / FT LF55.250 / FAN LF55.250 (Euro 3)	
Year	(2001>2006)		(2001>2006)		(2001>2006)	
Engine Type	Paccar BE 99C (Euro 3) Paccar BE 110C (Euro 3) Paccar BE 123C (Euro 3)		Paccar BE 99C (Euro 3) Paccar BE 110C (Euro 3) Paccar BE 123C (Euro 3)		Paccar CE 136C (Euro 3) Paccar CE 162C (Euro 3) Paccar CE 184C (Euro 3)	
CV(kW) @ rpm	135 (99) @ 2.500 150 (110) @ 2.500 167 (123) @ 2.500		135 (99) @ 2.500 150 (110) @ 2.500 167 (123) @ 2.500		185 (136) @ 2.500 220 (162) @ 2.500 250 (184) @ 2.500	
N. of cylinders/cm3	4 / 3.900		4 / 3.900		6 / 5.900	
Volts	24		24		24	
Air Conditioning	Only Vehicles without A/C		Vehicles with or without A/C		Only Vehicles without A/C	
Recommended fittings	Suction 	Discharge 	Suction 	Discharge 	Suction 	Discharge 
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15	
Comments	<ul style="list-style-type: none"> - "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15. - Can be fit in right hand drive vehicles. - A 45° suction fitting is recommended on right hand drive vehicles. 		<ul style="list-style-type: none"> - Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles 		<ul style="list-style-type: none"> - "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15. - Can be fit in right hand drive vehicles. - A 45° suction fitting is recommended on right hand drive vehicles. 	
Clutch type	<i>Without clutch pulley</i>	<i>With clutch pulley</i>	<i>Without clutch pulley</i>		<i>Without clutch pulley</i>	<i>With clutch pulley</i>
	Poly-V 8K Ø119 3.782 rpm	Poly-V 8K Ø157 2.886 rpm	2A Ø135 3.480 rpm		Poly-V 8K Ø119 3.782 rpm	Poly-V 8K Ø157 2.886 rpm
Kit No.	KC05100025	KC05100025E/S	KC05100026		KC05100025	KC05100025E/S
Last update	2013-12-18		2013-12-18		2013-12-18	

Vehicle model	FA LF45.180 / FA LF55.180 / FT LF55.180 / FAN LF55.180 FA LF45.220 / FA LF55.220 / FT LF55.220 / FAN LF55.220 FA LF55.250 / FT LF55.250 / FAN LF55.250 (Euro 3)			
Year	(2001>2006)			
Engine Type	Paccar CE 136C (Euro 3) Paccar CE 162C (Euro 3) Paccar CE 184C (Euro 3)			
CV(kW) @ rpm	185 (136) @ 2.500 220 (162) @ 2.500 250 (184) @ 2.500			
N. of cylinders/cm3	6 / 5.900			
Volts	24			
Air Conditioning	Vehicles with or without A/C			
Recommended fittings	<i>Suction</i>	<i>Discharge</i>		
				
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15			
Comments	- Not to be used on 18 ton vehicles - Can be fit in right hand drive vehicles			
Clutch type	Without clutch pulley			
	2A Ø135 3.480 rpm			
Kit No.	KC05100026			
Last update	2013-12-18			